

Dome Camera DBD 1540360

Special features:

Horizontal Resolution of over 600TV Line // Wide Angle 180° Panorama views // Lens Distortion Compensation // Multiple Image Areas // Anti-vandal camera body and dome cover



Technical data

A.004.820.07.97

Image Sensor	1/3" WDR CMOS Sensor
Scanning system	Progressive
Min. illumination	0.1LuX / F2.0
Horizontal Resolution	600 TVL
Total Pixels	1312(H) x 828(V) = 1,086,336 (pixel)
S/N Ratio	More than 39dB (AGC off)
View	NORMAL / ORIGINAL / TOP VIEW / PANORAMA / NOR-2WIN / NOR-3WIN
Lense	ELC
Power	DC12V±10%
Power consumption	Max. 1.5W (120mA)
Shutter	Rolling shutter
Brightness	0 ~ 100 steps
AGC	0 ~ 15 steps
Back light	OFF / BLC / WDR
BLC	LOW / MIDDLE / HIGH
WDR	LOW / MIDDLE / HIGH
Day & Night	AUTO / COLOR / B&W / EXT HIGH / EXT LOW
Day & Night Level	Support

Dome Camera DBD 1540360

More Technical data

A.004.820.07.97

Day & Night Delay	0 ~ 60 steps
White balance	AUTO / MANUAL
Sharpness	0 ~ 15 steps
Reverse	OFF / H REV / V REV / HV REV
Freeze	OFF / ON
Colour Gain	0 ~ 5 steps
D-Zoom	AUTO / MANUAL (1.0x ~ 10.0x)
ePTZ	Support
CAM ID	0 ~ 255
Baud rate	2400 / 4800 / 9600 / 19200 / 38400
Protocol	PELCO-D
UTC	Support (RJ102/RJ ELECTRONICS)
Video out	CVBS, NTSC / PAL
Privacy	8 Zone
2D DNR	OFF / ON
Language	ENGLISH
Display	CAM ID, ZOOM MAG
Reset	FACTORY
Audio	Support
Operating Temperature	-10°C ~ +50°C
Storage Temperature	-20°C ~ +60°C
Measurement(mm)	75(D)x 66(L)
Weight(Approx. g)	300

BILEXA AG

Vertriebs- und Vermietungs Ges.m.b.H.
Steinwiesen 4
A-6824 SCHLINS
Tel.: 05524-8430
Fax: 05524-8430-12
www.bilexa-ag.com
schlins@bilexa-ag.com

BILEXA AG

Sihlrainstrasse 18
CH-8002 Zürich
Tel.: 01-2082020
Fax: 01-2082022
www.bilexa-ag.com
zuerich@bilexa-ag.com